

DEPARTMENT OF THE ARMY  
US Army Corps of Engineers  
Washington, DC 20314

EM 1110-3-136

Engineer Manual  
No. 1110-3-136

9 April 1984

Engineering and Design  
DRAINAGE AND EROSION CONTROL  
Mobilization Construction  
PART ONE  
GENERAL

	<u>Paragraph</u>	<u>Page</u>
CHAPTER 1. PURPOSE AND SCOPE		
Purpose.....	1-1	1-1
Scope.....	1-2	1-1
Hydrologic cycle.....	1-3	1-1
CHAPTER 2. DESIGN CONSIDERATIONS		
Design.....	2-1	2-1
Drainage outfall considerations...	2-2	2-1
Initial and deferred design and construction.....	2-3	2-1
PART TWO SUBSURFACE DRAINAGE		
CHAPTER 3. SUBSURFACE DRAINAGE REQUIREMENTS		
General.....	3-1	3-1
Investigations to determine subsurface drainage requirements.	3-2	3-1
Criteria for determining the need for subsurface drainage.....	3-3	3-2
CHAPTER 4. PRINCIPLES OF SOIL DRAINAGE		
Flow of water through soils.....	4-1	4-1
Drainage of water from soils.....	4-2	4-4
CHAPTER 5. BACKFILL FOR SUBSURFACE DRAINS		
General.....	5-1	5-1
Empirical design of filter materials.....	5-2	5-1
Construction of filter material....	5-3	5-3

	<u>Paragraph</u>	<u>Page</u>
CHAPTER 6. SUBSURFACE DRAINAGE PROCEDURES		
Purpose.....	6-1	6-1
Methods.....	6-2	6-1
Base- and subbase-course drainage.....	6-3	6-1
Subgrade drainage.....	6-4	6-3
Intercepting drainage.....	6-5	6-6
Type of pipe.....	6-6	6-6
Manholes and observation basins....	6-7	6-9
Pipe sizes and slopes.....	6-8	6-9
Filter material.....	6-9	6-10
Depth of cover over drains.....	6-10	6-10
PART THREE		
SURFACE DRAINAGE		
CHAPTER 7. SURFACE DRAINAGE REQUIREMENTS		
General.....	7-1	7-1
Design storm.....	7-2	7-1
Infiltration.....	7-3	7-4
Rate of supply.....	7-4	7-4
Runoff.....	7-5	7-5
Investigations to determine..... surface drainage requirements...	7-6	7-9
CHAPTER 8. DRAINAGE PIPE		
General.....	8-1	8-1
Selection of type of pipe.....	8-2	8-1
Selection of n values.....	8-3	8-1
Restricted use of bituminous coated pipe.....	8-4	8-1
Minimum cover.....	8-5	8-3
Frost condition considerations.....	8-6	8-6
Infiltration of fine soils through drainage pipe joints.....	8-7	8-15
CHAPTER 9. INLETS AND BOX DRAINS		
General.....	9-1	9-1
Inlets versus catch basins.....	9-2	9-1
Design features.....	9-3	9-1
Box drains.....	9-4	9-6
Settlement of inlets and drains....	9-5	9-6

	<u>Paragraph</u>	<u>Page</u>
CHAPTER 10.	OPEN CHANNELS	
	General.....	10-1 10-1
	Channel design.....	10-2 10-1
	Design problem.....	10-3 10-3
CHAPTER 11.	CULVERTS	
	General.....	11-1 11-1
	Culvert flow.....	11-2 11-1
	Procedure for selection of culvert size.....	11-3 11-12
	Instructions for use of inlet-control nomographs.....	11-4 11-17
	Instructions for use of outlet-control nomographs.....	11-5 11-18
	Culvert capacity charts.....	11-6 11-19
CHAPTER 12.	CONSTRUCTION DRAINAGE	
	General.....	12-1 12-1
	Planning.....	12-2 12-1
	Protective measures.....	12-3 12-1
PART FOUR		
EROSION CONTROL		
CHAPTER 13.	EROSION CONTROL REQUIREMENTS	
	General.....	13-1 13-1
	Design criteria.....	13-2 13-1
	Estimating erosion.....	13-3 13-1
CHAPTER 14.	RIPRAP	
	Riprap protection.....	14-1 14-1
	Failures.....	14-2 14-1
	Stone size.....	14-3 14-1
	Design.....	14-4 14-4
CHAPTER 15.	VEGETATION	
	Planting zones.....	15-1 15-1
	Turf development.....	15-2 15-1
	Terraces.....	15-3 15-3

PART FIVE  
DEFERRED DESIGN AND CONSTRUCTION

	<u>Paragraph</u>	<u>Page</u>
CHAPTER 16. REQUIREMENTS FOR DEFERRED STRUCTURES		
General.....	16-1	16-1
Repairs.....	16-2	16-1
CHAPTER 17. HEADWALLS		
General.....	17-1	17-1
Entrances.....	17-2	17-1
Types of headwalls.....	17-3	17-1
Headwall construction.....	17-4	17-2
Outlets and endwalls.....	17-5	17-2
Structural stability.....	17-6	17-2
Sloughing.....	17-7	17-3
Apron.....	17-8	17-3
CHAPTER 18. DROP STRUCTURES AND CHECK DAMS		
Description and purpose.....	18-1	18-1
Design.....	18-2	18-1
Typical design problem.....	18-3	18-3
Solution - design of notch.....	18-4	18-3
Alternate design.....	18-5	18-4
CHAPTER 19. CHUTES		
General.....	19-1	19-1
Design problem.....	19-2	19-4
Solution.....	19-3	19-4
CHAPTER 20. STILLING BASINS		
General.....	20-1	20-1
Stilling well.....	20-2	20-1
USBR Type VI basin.....	20-3	20-3
SAF basin.....	20-4	20-3
Design summary.....	20-5	20-8
Comparison of various stilling basins.....	20-6	20-10
Design problem.....	20-7	20-10
Solution.....	20-8	20-12
CHAPTER 21. GUTTERS		
General.....	21-1	21-1

	<u>Paragraph</u>	<u>Page</u>
Discharge capacity.....	21-2	21-1
Design charts.....	21-3	21-1
APPENDIX A	SUPPORTING INFORMATION FOR CULVERT DESIGN	A-1
APPENDIX B	REFERENCES	B-1

## LIST OF FIGURES

Figure 1-1.	Occurrence, source, and movement of ground water.
4-1.	Darcy's Law for flow-through soils.
4-2.	Permeability chart.
4-3.	Design of base- and subbase-course drainage.
5-1.	Design example for filter material.
6-1.	Typical details of base- and subbase-course drain installations.
6-2.	Typical subgrade drainage details.
6-3.	Ground water conditions after installation of subgrade drainage.
6-4.	Thickness of ground water layer in relation to shape factor.
6-5.	Typical installation of intercepting drains.
6-6.	Drainage nomograph.
7-1.	Design storm index - 1 hour rainfall intensity frequency data for continental United States and Alaska.
7-2.	Standard rainfall intensity duration curves or standard supply curves.
7-3.	Modification in L required to compensate for differences in n and S.
7-4.	Rate of overland flow.
8-1.	Three main classes of conduits.
8-2.	Free-body conduit diagrams.
8-3.	Load factors and class of bedding.
8-4.	Bedding for positive projecting conduits.
8-5.	Installation conditions which influence loads on underground conduits.
8-6.	Relationships between air freezing index and frost penetration into granular, nonfrost-susceptible soil beneath pavements kept free of snow and ice for freezing indexes below 800.
8-7.	Relationships between air freezing index and frost penetration into granular, nonfrost-susceptible soil beneath pavements kept free of snow and ice.
8-8.	Maximum depth of frost penetration.
9-1.	Determination of typical inlet grating discharge curve.
9-2.	Examples of typical inlet grates.

9 Apr 84

- 9-3. Examples of inlet design.
- 9-4. Typical inlet box drain designs for airfield and heliport storm drainage systems.
- 10-1. Retardance coefficients for flow in turfed channels.
- 10-2. Airfield runway, taxiway, apron, and overrun grades.
- 10-3. Froude number and depth of flow required for incipient transport of cohesionless material.
- 10-4. Depth of flow and unit discharge for incipient transport of cohesionless material.
- 10-5. Flow characteristics of trapezoidal channels with 1-on-3 side slopes.
- 10-6. Froude number and depth of flow for incipient failure of riprap lined channel.
- 10-7. Depth of flow and unit discharge for incipient failure of riprap lined channel.
- 10-8. Flow characteristics of rectangular channels.
- 10-9. Discharge characteristics of various channels.
- 11-1. Inlet and outlet control.
- 11-2. Headwater depth for smooth pipe culverts with inlet control.
- 11-3. Headwater depth for corrugated pipe culverts with inlet control.
- 11-4. Headwater depth for box culverts with inlet control.
- 11-5. Head for smooth pipe culverts flowing full  $n = 0.012$ .
- 11-6. Head for corrugated pipe culverts flowing full  $n = 0.024$ .
- 11-7. Head for concrete box culverts flowing full  $n = 0.012$ .
- 11-8. Circular pipe critical depth.
- 11-9. Critical depth rectangular section.
- 11-10. Culvert capacity circular smooth pipe groove-edge entrance 18" to 66".
- 11-11. Culvert capacity standard circular corrugated pipe projecting entrance 18" to 36".
- 11-12. Culvert capacity standard circular corrugated pipe projecting entrance 36" to 66".
- 13-1. Square culvert-Froude number.
- 13-2. Predicted scour depth versus observed scour depth.
- 13-3. Predicted scour width versus observed scour width.
- 13-4. Predicted scour length versus observed scour length.
- 13-5. Predicted scour volume versus observed scour volume.
- 13-6. Dimensionless scour hole geometry for minimum tailwater.
- 13-7. Dimensionless scour hole geometry for maximum tailwater.
- 14-1. Recommended riprap sizes, gully scour.
- 14-2. Recommended riprap sizes, scour hole.
- 14-3. Recommended gradation.
- 15-1. Planting zones.
- 17-1. Maximum permissible discharge for various lengths of flared outlet transition and tailwaters.

- 17-2. Length of flared outlet transition relative to discharge, tailwater, and conduit size.
- 17-3. Relative effects of recessed apron and end sill on permissible discharge.
- 18-1. Design of drop structures for open channels.
- 18-2. Details and design chart for typical drop structure.
- 19-1. Details of typical drainage chute.
- 19-2. Design charts for concrete drainage chute.
- 20-1. Stilling well.
- 20-2. Storm drain diameter versus discharge stilling well.
- 20-3. USBR Type VI basin.
- 20-4. Storm drain diameter versus discharge USBR Type VI basin.
- 20-5. Proportions of SAF stilling basin.
- 20-6. Storm drain diameter versus discharge SAF stilling basin.
- 20-7. Design chart for SAF stilling basin.
- 21-1. Drainage gutters for runways and aprons.
  - A-1. Headwater depth for oval smooth pipe culverts, long axis vertical with inlet control.
  - A-2. Headwater depth for oval smooth pipe culverts, long axis horizontal with inlet control.
  - A-3. Headwater depth for structural plate and corrugated pipe-arch culverts with inlet control.
  - A-4. Headwater depth for corrugated pipe culverts with tapered inlet, inlet control.
  - A-5. Headwater depth for circular pipe culverts with beveled ring, inlet control.
  - A-6. Head for oval smooth pipe culverts long axis horizontal or vertical flowing full  $n = 0.012$ .
  - A-7. Head for structural plate pipe culverts flowing full  $n = 0.0328$  to  $0.0302$ .
  - A-8. Head for corrugated pipe-arch culvert flowing full  $n = 0.024$ .
  - A-9. Head for field-bolted structural plate pipe-arch culverts 18-inch corner radius flowing full  $n = 0.0327$  to  $0.0306$ .
  - A-10. Oval smooth pipe long axis horizontal critical depth.
  - A-11. Oval smooth pipe long axis vertical critical depth.
  - A-12. Corrugated pipe-arch critical depth.
  - A-13. Structural plate pipe-arch critical depth.
  - A-14. Culvert capacity circular smooth pipe groove-edged entrance 60" to 180".
  - A-15. Culvert capacity standard circular corrugated pipe headwall entrance 18" to 36".
  - A-16. Culvert capacity standard circular corrugated pipe headwall entrance 36" to 66".
  - A-17. Culvert capacity standard corrugated pipe-arch projecting entrance 25" by 16" to 43" by 27".

- A-18. Culvert capacity standard corrugated pipe-arch projecting entrance 50" by 31" to 72" by 44".
- A-19. Culvert capacity standard corrugated pipe-arch headwall entrance 25" by 16" to 43" by 27".
- A-20. Culvert capacity standard corrugated pipe-arch headwall entrance 50" by 31" to 72" by 44".
- A-21. Culvert capacity square concrete box 90 degrees and 15 degrees wingwall flare 1.5' by 1.5' to 7' by 7'.
- A-22. Culvert capacity square concrete box 30 degrees and 75 degrees wingwall flare 1.5' by 1.5' to 7' by 7'.
- A-23. Culvert capacity rectangular concrete box 90 degrees and 15 degrees wingwall flare 1.5', 2.0', and 2.5' heights.
- A-24. Culvert capacity rectangular concrete box 90 degrees and 15 degrees wingwall flare 3' and 4' heights.
- A-25. Culvert capacity rectangular concrete box 90 degrees and 15 degrees wingwall flare 5' and 6' heights.
- A-26. Culvert capacity rectangular concrete box 30 degrees and 75 degrees wingwall flare 1.5', 2.0', and 2.5' heights.
- A-27. Culvert capacity rectangular concrete box 30 degrees and 75 degrees wingwall flare 3' and 4' heights.
- A-28. Culvert capacity rectangular concrete box 30 degrees and 75 degrees wingwall flare 5' and 6' heights.

#### LIST OF TABLES

- Table 7-1. Infiltration rate for generalized soil classifications (uncompacted).
- 7-2. Coefficients of roughness for overland flow.
  - 8-1. Roughness coefficients for various pipes.
  - 8-2. Minimum pipe cover requirements for airfields and heliports.
  - 8-3. Minimum pipe cover requirements for roads and railroads.
  - 8-4. Minimum required depth of cover protection of storm drains and culverts in seasonal frost areas.
  - 8-5. Estimated frost penetration for selected locations.
  - 10-1. Suggested coefficients of roughness and maximum permissible mean velocities for open channels.
  - 11-1. Entrance loss coefficients outlet control, full or partly full entrance head loss  $W_e = K_e V^2/2g$ .
  - 11-2. Manning's  $n$  for natural stream channels.
  - 17-1. Limiting values of  $Q/D_o^{5/2}$ .



EM 1110-3-136  
9 Apr 84

- 20-1. Maximum discharge recommended for various types and sizes of energy dissipators.